

GB020120

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-341549
(43)Date of publication of application : 10.12.1999

(51)Int.Cl.

H04Q 7/34
H04B 7/26
H04Q 7/38

(21)Application number : 10-146133 (71)Applicant : ALPS ELECTRIC CO LTD
(22)Date of filing : 27.05.1998 (72)Inventor : CHISHIMA TAKESHI
FUJIO KENICHI

(54) METHOD FOR GENERATING POSITION DETECTION TERMINAL DATA IN MOBILE COMMUNICATION SYSTEM
(57)Abstract:

PROBLEM TO BE SOLVED: To provide a method for generating position detection terminal data in the mobile communication system that avoids problems of dispersion by figuring out an input level that takes a characteristic of an RSSI voltage due to the dispersion in an IC for each terminal.

SOLUTION: A standard signal generator generating a signal with a desired input level connects to each terminal in the mobile communication system in advance, a modulation signal for each of plural input levels is received, the modulation signal is given to a demodulator, where the signal is converted into an RSSI voltage and an A/D converter converts the voltage into an A/D conversion value, it is stored in a ROM of each terminal, where a virtual data curve interconnecting the A/D conversion values for each input level through linear interpolation is generated and the strength of a radio wave sent from the base station and received by the terminal is adapted to the data curve to generate the position detection terminal data.

LEGAL STATUS

[Date of request for examination]
[Date of sending the examiner's decision of rejection]
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office